




E-E (1 : 2)



191
1 to be used during assembly of the inverted pendulum

| | | | |
|--|--------------|-----------------------|-------------|
| | | added part 191.1 | 06-06-11 |
| | | modified part 189 | 02-06-11 |
| | | modified part 189 | 19-05-11 |
| | | modified part 190-191 | 13-05-11 |
| ref. | | note | date |
| modifications | | | |
| 191.1 | 3 | AISI 394 | 1:1 |
| 191 | 3 | Bronze B14 | 1:1 |
| 190 | 3 | AISI 304 | 1:2 |
| 189 | 3 | AISI 304 L | 1:2 |
| ref. | pieces | material | scale |
| GENERAL TOLERANCE mK | | | |
| TOLERANCE SYSTEM: ISO 2768-2 CLASS H-K-L | | | |
| | DESIGNED FOR | | R. De Salvo |
| | DRAW. BY | | G. Gennaro |
| | DATE | | 21-03-11 |
| | SCALE | | 1:1 |
| N° DRAW. | | LCGT.0109-04 | |
| REPLACE DRAW N° | | 0111 | |
| DETAIL FROM | | 0100 | |
| TITLE | | | A2 |
| LCGT-SAS | | | |
| DETAILS Gr.1 | | | |