


NOTE: The damper mounts only on filter 1 of each chain.  
Filter 1 in type-A chain has 12 blades.  
Filter 1 in type-B1 chain has 4 blades.  
Filter 1 in type B2 chain has 6 blades.  
In type-B the missing blade assemblies (draw. 0201) are replaced by transport plates (part 506) mounted only two screws in the inner diameter positions.

See general screw's list at draw. 0217

Elenco parti			
ELEMENTO	QTÀ	NUMERO PARTE	DESCRIZIONE
11	8	ISO 4762 - M10 x 25	Viti con esagono incassato
84	15	ISO 4762 - M5 x 20	Viti con esagono incassato
85	9	UNI 5933 - M6 x 35	Vite svasata
84	6	ISO 4762 - M4 x 10	Vite con esagono incassato
88	3	ISO 4762 - M6 x 40	Vite con esagono incassato

This symbol show position screws

	Added note	1-02-12
	Changed references	1-02-12
ref.	note	date
modifications		
506	10013	Security clamp for transport
369	10013	Connection suspension wire
368	10013	Cone guide
367	10013	Support magnets damper
366	10013	Ring damper
365	10013	Spacer damper system
	0200	Standard filter with 4 or 6 blades
ref.	draw.	legend



**PROMEC**  
di Gennaro Gianni  
BIENTINA (PISA)-ITALIA

DESIGNED FOR  
**R. De Salvo**

DESIGN  
**G. Gennaro**

DATE  
**17-12-11**

SCALE  
**1:4**

TITLE  
**LCGT-SAS**  
MAGNETIC DAMPER FOR  
STANDARD FILTER-Gr. 10

ASS. NUM.  
**LCGT.10004-02**

REV. 01  
From 10001

**A1**