


NOTE: The damper mounts only on filter 1 of each chain.
Filter 1 in type-A chain has 12 blades.
Filter 1 in type-B1 chain has 4 blades.
Filter 1 in type B2 chain has 6 blades.
In type-B the missing blade assemblies (draw. 0201) are replaced by transport plates (part 506) mounted only two screws in the inner diameter positions.

See general screw's list at draw. 0217

Elenco parti			
ELEMENTO	QTÀ	NUMERO PARTE	DESCRIZIONE
11	8	ISO 4762 - M10 x 25	Viti con esagono incassato
84	21	ISO 4762 - M5 x 20	Viti con esagono incassato
88	3	ISO 4762 - M6 x 40	Vite con esagono incassato
90	12	DIN 7991 - M5x12	Viti a testa svasata con impronta a croce ed esagono incassato
91	18	DIN 7991 - M5x12	Viti a testa svasata con impronta a croce ed esagono incassato

This symbol show position screws

		Updated	18-04-12
		Added note	1-02-12
		Changed references	1-02-12
ref.		note	date
modifications			
583	10013	Joint part 366	
506	10013	Securiry clamp for transport	
369	10013	Connection suspension wire	
368	10013	Cone guide	
367	10013	Support magnets damper	
366	10013	Arc damper	
365	10013	Spacer damper system	
	0200	Standard filter with 4 or 6 blades	
ref.	draw.	legend	



PROMEC
di Gennaro Gianni
BIENTINA (PISA)-ITALIA

DESIGNED FOR
R. De Salvo
DESIGN
G. Gennaro
DATE
17-12-11
SCALE
1:4
ASS. NUMB.
LCGT.10004-03
REVISIONE
From 10001

LCGT-SAS
MAGNETIC DAMPER FOR
STANDARD FILTER-Gr. 10

A1