

# KAGRA用防振装置の開発 VIII

高橋竜太郎、山元一広、関口貴令、内山隆、宮川治、上泉眞裕(東大宇宙線研究所)

石崎秀晴(国立天文台) 高森昭光(東大地震研究所)


R. DeSalvo (Univ. of Sannio) E. Majorana (INFN Rome)

J. van den Brand, E. Hennes, A. Bertolini (NIKHEF)

N. Lockerbie (Univ. Strathclyde)

KAGRA collaboration



1. Configuration
2. Sensors and Actuators
3. Schedule and Status
4. Summary



2012年秋季大会  
於 京都産業大学

# 1. Configuration

# Seismic Attenuation System **SAS** (Type-A/B)



# Configuration



Type-A: IP + GASF (5 stage) + Payload (23kg, cryogenic)

Type-B: IP + GASF (3 stage) + Payload (10kg/20kg)



Type-C: Stack + Single/Double-pendulum (~1kg)

Chamber	iKAGRA	bKAGRA
IXV, IYV, EXV, EYV		Type-A
IXA, IYA, EXA, EYA	Type-B Payload on rigid table (for ITM/ETM)	
BS, PR2, PR3	Type-B (Only payload is free, other parts are not used)	Type-B
PRM, SRM, SR2, SR3		Type-B
MCF, MCE, IFM, IMM	Type-C	Type-C
OFL, OMC, EXT, EYT		Type-C

# Type-A




## Type-B




## Type-B payload on rigid table

Type-C




## 2. Sensors and Actuators



# Pre-isolator




# Type-B Payload



# Optical Sensor and Electro-Magnetic actuator (OSEM)





The linear range is  $\sim 1\text{mm}$ .



The sensitivity is  $\sim 2.5 \times 10^{-10} \text{ m/Hz}^{1/2}$  at 1 Hz, and  $\sim 7 \times 10^{-10} \text{ m/Hz}^{1/2}$  at 0.1 Hz.

### 3. Schedule and Status

# Schedule



## Current task




- Prototype test of the pre-isolator in Kashiwa
- Assembling of the GAS filters in Akeno

## Order in 2012FY

- Payload prototype: June
- 6 Pre-isolators: October

# Test of pre-Isolator prototype

detail: 11aSN3



Motor sliders and LVDT-actuator modules were assembled onto the IP with cabling.

The level of the IP base was tuned using the hydraulic piston.

# Storage & Assembling in Akeno

- The 19 GAS filters have been delivered in February, 2012.
- The clean booth is ready for assembling.
- Final tuning will be started soon.



# Manufacturing of payload prototype

- The payload prototype has been delivered in August, 2012.
- Assembling and tests will be started soon.



## 4. Summary

- The seismic attenuation system (SAS), which consists of inverted pendulum (IP) and geometric anti-spring (GAS) filter, is used in KAGRA.
- Three kinds of isolation system are used depending on required specifications.
- Sensors and actuators are embeded onto each stage of the isolation system for local and global controls.
- Test of prototypes and production of instruments for iKAGRA are now going.