



Present status of the laser system


Ryota Nishiuchi, Ken-ichiro Suzuki
University of Tokyo
Photon Science Center
Mio laboratory

Outline

- **Background**
 - Laser system & Requirements
 - Intensity noise
 - Frequency noise
 - High-power output of solid-state amplifier
 - Control system
- **Present setup**
 - Fiber optics
 - Coherent addition
 - Solid-state amplifier
- **Experimental results**
 - High-power output of coherent addition
 - Long-term operation
- **Summary & Future work**

Laser system & requirements


Requirements		
• Laser power	180 W	• Linear polarization
• Single frequency	1064 nm	• Low intensity noise
• Single transverse mode	TEM ₀₀	• Low frequency noise



- MOPA
 - Fiber amplifier
 - Solid-state amplifier
- Coherent addition
 - Phase correction is maintained by fiber stretcher


Present setup – fiber optics

Fiber amplifiers




Fiber components

- Isolator
- Coupler
- Polarizer
- EOM
- Stretcher



Seed laser


NPRO 400 mW




➔ 40W

➔ 40W

Present setup – coherent addition




Present setup – solid-state amplifier




Coherent addition output

80W →



180W



Solid-state amplifier




- 3 modules in the system
- One module has 2 YAG rods and 16 LD arrays
- 50 W amplification / module is expected

Result High-power output of coherent addition

- 78.9 W was obtained by coherent addition
- This is instant value, not stable





Bright port



Dark port

Result Long-term operation




- Operation time was extended
 - 5 \rightarrow 8 hours
- Coherent addition power was declined after 4 hours operation
 - Due to amp A ?
- Temperature change

Result

WF distortion


- Wave front distortion was measured before and after coherent addition
- Low-order components (0th, 1st and defocus) of Zernike polynomials are eliminated



Distortion	A	B	80W A+B
Standard deviation [nm]	31.8	35.1	31.6

Result



Intensity noise after coherent addition





- Intensity noise becomes worse after amplification and coherent addition
- Bumping at 2-3 kHz is due to NPRO
- Bumping at 8-10 kHz is due to fiber amplifiers
- Noise peak in 18 kHz on coherent addition signal

Fiber stretcher

- Wide control range (max $\pm 2240 \mu\text{m}$ @ $\pm 400\text{V}$)
- Using 2 stretchers differentially
 - Extend the dynamic range
- Mechanical resonance
 - Limit the control bandwidth




http://www.optiphase.com/data_sheets/PZ2_Data_Sheet_Rev_F.pdf




Result Phase noise



- Laser frequency was locked to rigid cavity with PZT on NPRO
- By using a vibration isolated table, seismic noise was declined
- By using vacuum chamber, sound noise was declined



- Noise floor was determined by NPRO
- Peak @ 18 kHz




Result Phase noise



- Noise peak in 18 kHz


Result High-power output of solid-state amplifiers

- 210 W was obtained by solid-state amplifiers
- Adjustment of optics is not perfect
- It is difficult to realize good alignment
 - Dangerous due to its high power
 - When the input beam power changes, thermal lensing effect in the laser module also changes



Result


Intensity noise after solid-state amplifier



- 18 kHz peak on noise of 200 W beam
- RIN of the 200 W beam is decreased at high frequency

Result


Intensity noise – comparison with previous work




N. Ohmae (2010). "Laser System for Second-Generation Gravitational-Wave Detectors"

- Comparison with previous work
 - Less intensity noise at some frequency range
- Peak @ 18 kHz

Result Control system




with old filter



with new filter

- Fiberstretcher + EOM
- Unity gain frequency is about 80 kHz

Result Control system



- Resonance peak was diminished

Summary & Future work

- 78.9 W was achieved by coherent addition
- 210 W was achieved by solid-state amplifiers
- Coherent addition was maintained for 8 hours
- Output power changed in time
- Atmosphere temperature changed in time
- 18 kHz noise peak was diminished

- Stabilize output power, frequency
 - Stabilize temperature?
- Evaluate the noise of the 210-W beam
- Interlock