

Based on D1503900-v5 (BS), D1503614-v2 (PR2), D1503917-v1 (EXA), D1503901-v1 (Cable Detail)

Bulk cable (m)				Connectors											
Gore	MWS	Ribbon	RJ22	DM9MV	DS9MV	DM9F	DS9M	DS9F	DS9M IDC	DS9F IDC	PDM	PDF	PBM	PBF	
EXA:			2 suspensions												
34.5	6	1.3	0.5	10	13	0	2	4	12	12	0	10	0	0	
PR2:			3 suspensions												
58.5	28.5	2	0.2	10	29	46	3	6	15	15	0	10	8	0	
BS:			1 suspension												
109.1	39.5	2.7	0.5	10	32	70	7	9	26	26	0	10	12	0	
Etc:			1												
Total:															
353.6	137	11.3	2.1	60	145	208	20	35	95	95	0	60	36	0	

			Etc	Cables (per D1503901)											
RJ22M	CI01M	10-6 F	Feedth ough	TM OSEM to BF (01)	IM OSEM to BF (02)	IM Pico Adapter (03)	BF Pico Adapter (04)	BF&SF Stepper Adapter (05)	BF&SF LVDT Adapter (06)	Geoph one Adapter (07)	BF to PI Signal (08)	SF to PI Signal (09)	Signal Cable Extensio n (10)	PI to Flange Signal (11)	
5	0	0	13	4	6	1	0	0	1	0	0	0	0	0	
5	2	0	20	4	6	1	1	1	2	0	0	0	0	0	
5	5	3	27	4	6	1	1	2	2	3	11	1	0	16	
30	11	3	113	24	36	6	4	5	10	3	11	1	0	16	

PI to Flange Geophone (12)	PI to Flange Motor (13)	BF to PI Motor (14)	SF to PI Motor (15)	Motor Cable Extension (16)	BF to TR Signal (17)	BF to TR Motor (18)	TR to Flange Signal (19)	TR to Flange Motor (20)	BF to Flange Signal (21)	BF to Flange Motor (22)	Pico+Stepper Adapter (23)	
0	0	0	0	0	0	0	0	0	0	11	2	1
0	0	0	0	0	11	3	12	8	0	0	0	0
3	8	3	1	0	0	0	0	0	0	0	0	0
3	8	3	1	0	33	9	36	24	22	4	2	2