



*注1: センター振り分けでない

公差等級	面取り部分を除く長さの基準寸法の区分と許容差						面取り部分の長さの基準寸法の区分と許容差				角度の基準寸法(対象とする角度の短い辺の長さ)の区分と許容差								
	0.5-3 mm	3-6 mm	6-30 mm	30-120 mm	120-400 mm	0.4-1 m	0.5-3 mm	3-6 mm	6 mm<	10 mm>	10-50 mm	50-120 mm	120-400 mm	400 mm<	10°	±30'	±20'	±10'	±5'
記号	0.5-3 mm	3-6 mm	6-30 mm	30-120 mm	120-400 mm	0.4-1 m	0.5-3 mm	3-6 mm	6 mm<	10 mm>	10-50 mm	50-120 mm	120-400 mm	400 mm<	10°	±30'	±20'	±10'	±5'
精度	±0.05	±0.05	±0.15	±0.1	±0.2	±0.3	±0.2	±0.3	±0.5	±1°	±30'	±20'	±10'	±5'					

NOTES AND TOLERANCES: (UNLESS OTHERWISE SPECIFIED)

1. MODIFIED DRAWING PER ASME Y6.11-2015
2. REMOVE ALL SHARP EDGES, .05 FOR MACHINED PARTS, ROUND ALL EDGES APPROXIMATELY R.02 FOR SHEET METAL PARTS.
3. DO NOT SCALE FROM DRAWING.
4. ALL MACHINING FLUIDS MUST BE FULLY SYNTHETIC, FULLY WATER SOLUBLE AND FREE OF SULFUR, SILICONE, AND CHLORINE.

MATERIAL PEEK VICTREX 450GL30 FINISH μmm

First Class Light Inc.		PART NAME ASC_AIR_nclosure - base	
SYSTEM	SUB-SYSTEM	DESIGNER H.Matsura	DWG. NO. JGW-E1504468-v0
		DRAFTER Y.Yamaguchi	modified from LIGO:D1101201
		CHECKER	REV. v0
NEXT ASSY		APPROVAL	SCALE: 1:1 PROJECTION: SHEET 1 OF 1