

# O3 Estimated Sensitivity for FPMI, PRFPMI and RSE

Yutaro Enomoto, Yuta Michimura

Department of Physics, University of Tokyo


Kentaro Somiya

Department of Physics, Tokyo Institute of Technology

# Conditions


- 10W input
- Shot noise coupling with feedforward gain 100 included
- Four IFO configurations
  - **FPMI with tilted PRM** (equivalent to 1W input power)
  - **FPMI with blank PRM**
  - **PRFPMI** ( $R_{SRM}=0\%$ )
  - **RSE with  $R_{SRM}=70\%$**
- Four excess noise models
  - No excess
  - aLIGO O1 level
  - 4x aLIGO O1 level (AdV O2 level)
  - 8x aLIGO O1 level
- Suspension and mirror thermal noise at 22 K

# Sensitivity with No Excess Noise




- thermal
- excess 0 x O1
- FPMI 1W (10W with PRM)**  
1.4-1.4 BNS: 18.0 Mpc  
30-30 BBH: 0.2349 Gpc
- FPMI 10W**  
1.4-1.4 BNS: 36.7 Mpc  
30-30 BBH: 0.4970 Gpc
- PRFPMI 10W**  
1.4-1.4 BNS: 57.9 Mpc  
30-30 BBH: 0.8215 Gpc
- RSE 10W, R\_SRM=70%**  
1.4-1.4 BNS: 93.4 Mpc  
30-30 BBH: 1.4323 Gpc

# Sensitivity with O1 Excess Noise





# Sensitivity with x4 O1 Excess Noise




- thermal
- excess 4 x O1
- FPMI 1W (10W with PRM)**  
 1.4-1.4 BNS: 9.5 Mpc  
 30-30 BBH: 0.1228 Gpc
- FPMI 10W**  
 1.4-1.4 BNS: 16.3 Mpc  
 30-30 BBH: 0.2137 Gpc
- PRFPMI 10W**  
 1.4-1.4 BNS: 27.1 Mpc  
 30-30 BBH: 0.3737 Gpc
- RSE 10W, R\_SRM=70%**  
 1.4-1.4 BNS: 41.6 Mpc  
 30-30 BBH: 0.6219 Gpc

# Sensitivity with x8 O1 Excess Noise




# Sensitivity at 300K




- ..... thermal 22K
- thermal 300K
- FPMI 1W (10W with PRM)
- 1.4-1.4 BNS: 3.1 Mpc
- FPMI 10W
- 1.4-1.4 BNS: 4.9 Mpc
- PRFPMI 10W
- 1.4-1.4 BNS: 6.9 Mpc
- RSE 10W, R\_SRM=70%
- 1.4-1.4 BNS: 11.6 Mpc

# Cryogenics: Necessary


- 300K suspension thermal noise is x100 worse



# Shot Noise Coupling **FPMI 1W**




# Shot Noise Coupling **FPMI 10W**




# Shot Noise Coupling PRFPMI

Shot Noise Coupling with Feed Forward





# Shot Noise Coupling RSE

Shot Noise Coupling with Feed Forward




# IR vs Power **FPMI**



Note: Shot noise coupling calculation is done only at 10 W and scaled with  $1/\sqrt{P}$

# IR vs Power PRPFMI/RSE



# Necessity

⊙: Necessary for locking


○: Can be omitted with extra work

△: Can be omitted with sensitivity degradation

×: Not necessary

Sensitivity (10W, x4 O1 excess)	RSE (42 Mpc)	PRFPMI (27 Mpc)	FPMI (9.5 / 16 Mpc)
ALS (green lock)	⊙	○	×
f3 AM (MZI)	⊙	○	×
Extra locking simulation	×	⊙	×
SRC ASC	⊙	×	×
SRM	⊙	○ (Blank or move OMMT)	○ (Blank or move OMMT)
OMC	△	△	△
Comment	SRC ASC might be tough	f1 will be 1/10, no SRC mode cleaning	PRM: tilt or blank or move IMMT No PRC jitter attenuation

# Sensitivity Comparison




# Sky Localization Calculation


- 10W input, x4 O1 excess noise
- Source parameters (GW170817-like, no spins)
  - redshift: 0.009 (~ 40 Mpc)
  - total/chirp mass: 2.74 / 1.188 Msun
  - inclination angle: 28 deg
  - source locations: equally distributed 648 locations
  - polarization angle: 3 angles
  - > 1944 realizations
- Waveform
  - PhenomD upto inspiral ([PRD 93, 044007 \(2016\)](#))
  - fmin=10Hz, fmax=fISCO~1.6 kHz
- Network sensitivity
  - aLIGO: Late Low (116 Mpc) [LIGO-P1200087](#)
  - AdV: Mid Low (63 Mpc) [LIGO-P1200087](#)
- Fisher analysis (see, also [JGW-T1808090](#))

# Sky Localization Map


FPMI\_1W ( $\psi_p = 0.0$  deg)




FPMI ( $\psi_p = 0.0$  deg)



PRFPMI ( $\psi_p = 0.0$  deg)




RSE ( $\psi_p = 0.0$  deg)




# Sky Localization Improvement Map

Improvement factor = HLVK / HLV


FPMI\_1W ( $\psi_p = 0.0$  deg)




FPMI ( $\psi_p = 0.0$  deg)



PRFPMI ( $\psi_p = 0.0$  deg)



RSE ( $\psi_p = 0.0$  deg)



# Sky Localization Distribution

Improvement factor =  $HLVK / HLV$

